

APPENDIX XI

Autocross Tech Inspection Sheet



Autocross Tech Inspection Sheet

NAME: _____ CLASS: _____ MEN'S LADIES'

YEAR/MODEL: _____ CAR COLOR: _____ CAR#: _____

Pass Fail

!!! entrant should check for compliance prior to bringing automobile to tech inspection for verification !!!

- | | | |
|-------|-------|---|
| _____ | _____ | 1. HELMET- SNELL SA, SAH, K or M 2000 or later required. Face shield required for cars without windshields. Snell SA, SAH, K or M sticker must be attached inside. |
| _____ | _____ | 2. SEAT BELTS/HARNESSES –Must be present and adequate. Where installation is other than factory design, the belt mounting must be securely anchored, metal-to-metal, with large diameter washers on both sides of floor mounting holes. Non-factory shoulder harnesses may be used in an open vehicle only if the automobile is equipped with a rollbar or cage. |
| _____ | _____ | 3. ROLL BARS/CAGES – Roll Bars are required in open vehicles driving in Modified classes, cages are optional. Rollbars/Cages must be equipped with adequate padding. Roll Bars/Cages, when required, must meet current PCR guidelines. |
| _____ | _____ | 4. BRAKE PEDAL – Free return and in good operating condition. Firm brake pedal. |
| _____ | _____ | 5. WINDSHIELDS/WINDOWS - No major cracks. Bolt-on windshields may be removed. |
| _____ | _____ | 6. GAS CAP – Gasket intact and cap tightened. |
| _____ | _____ | 7. RUST – No rust or damage to suspension or chassis parts that affect the integrity of the chassis or brakes. |
| _____ | _____ | 8. STEERING and SUSPENSION – No excessive looseness in steering or suspension. Axle and shock bolt tight. Ball joints in good condition. Tie rods secure. Axle boots and oil seals in good condition. Check half-shaft bolts and shock bolts. |
| _____ | _____ | 9. CAMBER – (356 automobiles) No positive camber on any car. |
| _____ | _____ | 10. WHEEL BEARINGS – Correct adjustment, check for play and no damage. |
| _____ | _____ | 11. WHEELS - No cracks. No bends. All lug nuts must be torqued to manufacturer’s specifications, minimum on diameter of engagement. Snap-on wheel covers and trim must be removed from steel wheels. |
| _____ | _____ | 12. TIRES – Must be free of visible sidewall cracks or belts showing. Clearance between tires and any potential rubbing point must be in compliance of chosen car class in the PCRs. |
| _____ | _____ | 13. BRAKE FLUID – Level in reservoir between min and max line. |
| _____ | _____ | 14. BATTERY – Securely fastened and in good condition. No acid leaks or corrosion. Check fuel lines under battery trays on 914's. The positive (+) terminal on all batteries should (optionally) be covered by cap or tape. |
| _____ | _____ | 15. EXHAUST – Must be in safe condition, no leaks, securely mounted. |
| _____ | _____ | 16. FLUID LEAKS – No fluid leaks of any kind. (oil, gas, brake, coolant or trans fluid) |
| _____ | _____ | 17. THROTTLE RETURN – Freely operating and good springs on cars so equipped. |
| _____ | _____ | 18. DOORS, HOOD AND DECK LIDS – Must fasten securely. |
| _____ | _____ | 19. CAR NUMBERS – Car numbers provided at Parade registration must be affixed on the front and both sides of the car. |

DRIVER'S SIGNATURE: _____ DATE: _____

WITNESS TO DRIVER'S SIGNATURE (Inspector): _____

SERVICE STAMP: _____ DATE: _____

Appendix XI